



ARMOR GUYS
• PROTECTED •

EXTRAFLEX



04-400 SPECIFICATION SHEET

ATTRIBUTES:

LINER

13g Orange Engineered
A4 Liner

COATING

Black HCT® MicroFoam
Nitrile Palm Coating

FEATURES:

- Reinforced Thumb Crotch
- MicroFoam Coating Ensures Excellent Oil Grip

APPLICATIONS:

- Automotive Manufacturing
- Metal Stamping
- Construction
- Sheet Metal Handling
- Steel Processing

Armor Guys reference number : 04-400

CATEGORY:

Extraflex

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

TECHNOLOGIES:



THUMB CROTCH
REINFORCEMENT



CUT
EN388



4442D



Tested for harmful substances
according to Oeko-Tex® Standard 100
SH400 098266 TESTEX

SPECIFICATIONS

LINER MATERIALS	13g Orange Engineered A4 Liner
COATING MATERIALS	Black HCT® MicroFoam Nitrile
WRIST DESIGN	Continuous Knit
SIZES	XS-XXXL

PACKAGING

CASE SIZE	XS	S	M	L	XL	XXL	XXXL
PER CARTON	10DZ	10DZ	10DZ	10DZ	10DZ	10DZ	10DZ
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue	Gray
ORIGIN	PRC						

PERFORMANCE LEVEL

EN388: 4442D	EN Level 4 Cut Resistance					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F